ROOF PAINT REFLECT WHITE

White reflective coating that renovates and cools







Product description

Ready-to-use white coating used to renovate both flat and sloping roofs and make them reflective.

Roof coverings treated with **ROOF PAINT REFLECT WHITE** will reflect UV rays and the sun's heat instead of absorbing it. A constant and lower temperature extends the life of the roofing. Reflection of the sun's heat by **ROOF PAINT REFLECT WHITE** results in more comfortable indoor temperatures and lower energy costs, due to lower energy consumption by cooling systems. It also increases the efficiency of installed solar panels. **ROOF PAINT REFLECT WHITE** is also a renovation coating that revitalises weathered bitumen roofing.

Application

For use on bitumen, metal, cement, tiles, slates and EPDM. **ROOF PAINT REFLECT WHITE** can also be applied to new bitumen roofs that are at least 6 months old.

Advantages

- Keeps your home cool
- Extends the life of the roofing
- Increases the efficiency of solar panels

How much product do I need?

Use approx. 1 litre per 4 m² per coat.

See also the calculator on our website <u>www.aquaplan.com</u>.

Handy tips?

- Shake well before use.
- Store between 5°C and 30°C.
- Clean your tools with white spirit or turpentine.
- Use **ROOF PRIMER MULTI** to prepare the roof. This will ensure optimum adhesion of **ROOF PAINT REFLECT WHITE**. Roof Primer Multi also forms a barrier between the bitumen substrate and the white coating.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Coating	White	1 L / 4 L	About 2 m²/L	About 24 hours	2	No

0116

ROOF PAINT REFLECT WHITE

White reflective coating that renovates and cools







What do I need?





How do I prepare the surface?

- Always work on a sound, clean, dust-free and dry surface.
- Apply **ROOF PRIMER MULTI** with a paint brush or roller at a rate of 0.15 l/m². Allow the primer to dry (at least 30 minutes) before proceeding.



How do I use the product?

- Apply a first coat of ROOF PAINT REFLECT WHITE with a paint brush or roller at a rate of 0.25 l/m².
- Allow the first coat to dry thoroughly before applying the second coat. The drying time (approx. 24 hours) depends on the temperature and weather conditions.
- Apply a second coat of ROOF PAINT REFLECT WHITE with a paint brush or roller at a rate of 0.25 l/m².











We are ready to answer all your questions. Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu Website: www.aquaplan.com







