

GARDEN PROTECT PAVEMENT

Protection for porous surfaces



PRODUCT DATA SHEET



Product description

Vapour-permeable, transparent surface protector for all absorbent and porous substrates in and around the home, such as paving stones and tiles. It creates a dirt, grease and water repellent surface. It revives the intensity of the substrate's original colour and shading and slows down the penetration of dust, grease and oil. Its moisture-resistant properties retard the growth of moss and algae and prevent frost damage. This greatly simplifies the maintenance of pavements.

Application

For use on all horizontal and vertical surfaces such as terraces, driveways, paths, façades, tombstones, statues, chimneys, etc. made of absorbent and porous materials such as paving stones and concrete tiles.

Advantages

- › One coat is sufficient
- › Revives colours
- › Dirt, grease and water repellent
- › Easy to apply

How much product do I need?

Use 1 litre for 1 to 4 m², depending on the porosity of the substrate. See also the calculator on our website www.aquaplan.com.

Handy tips?

- Store in a cool (max. 20°C) and frost-free place.
- Do not apply if the ambient or substrate temperature is below +10°C or above +35°C or if rain, frost or fog are expected within the first 8 hours.
- Clean your tools with water immediately after use.

Material	Colour	Contents	Coverage	Drying time	Coats	Overpaintable
Resin	Transparent	5 L / 10 L	0.25 to 1 l/m ² depending on the porosity of the substrate	About 6 hrs	1	Yes

GARDEN PROTECT PAVEMENT

Protection for porous surfaces



INSTRUCTIONS



What do I need?




How do I prepare the surface?

- First remove any dust and grease from the substrate. If the substrate is very dirty, clean it with a pressure washer. Remove any grease stains.
- Treat any green mould, lichens and algae with **GARDEN CLEAN GREEN REMOVER** or **GARDEN CLEAN SCRUB FREE**.
- Repair any damaged grouting.



How do I use the product?

- Shake **GARDEN PROTECT PAVEMENT** well before use. Test it on an inconspicuous area first. Can be applied on slightly damp substrates.
- Apply one undiluted coat of **GARDEN PROTECT PAVEMENT** to porous materials using a brush, roller or garden sprayer until the substrate is saturated. Prevent the formation of puddles. The amount of product required depends on the porosity of the substrate.
- Allow the product to dry for at least 4 hours and ensure that it is not exposed to rain for 8 hours.
- Garden Protect Pavement provides optimal protection after 7 days.



Would you like more information?

We are ready to answer all your questions.

Feel free to contact us:

Belgium: 03 248 30 00 or info@aquaplan.com

The Netherlands: 0162 42 29 00 or verkoop-dhz@martensgroep.eu

Website: www.aquaplan.com

